



## ACE FL22 EXTENDED LIFE COOLANT/ ANTIFREEZE

### PRODUCT DESCRIPTION:

ACE FL22 is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without amines and silicates. This product is formulated based on a proven inhibitor development as an extended life radiator antifreeze.

### APPLICATION:

ACE FL22 is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

### FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Universal application at passenger cars and commercial vehicles.
- Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump.
- Prevents the buildup of deposits, keeping the cooling system clean.
- Long life service product

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

GM 08CLAG01050 Honda E Coolant, Ford VC-10-A2, Hyundai 00232-19010, Hyundai 07100-00200, Hyundai 07100-00400, Hyundai Long Life Coolant, Mazda 000077508E20, Mazda C100CL005A4X, Mazda C122CL005A4X, Mazda FL22 Coolant, Nissan Anti-freeze Coolant (L250), Nissan KE90299934, Nissan KE90299944, Subaru Coolant 16218, Suzuki Longlife Coolant, WSS-M97B55.

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	ACE FL22
pH	D1278	cSt	8
Freezing Point	D1177	°C	-40
Boiling Point	D1120	cSt	110
Density at 15.5C	D4052	g/cm3	TBR

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.