



## AGROL STOU MINERAL

### PRODUCT DESCRIPTION:

Agrol Stou is a high-performance multi-functional oil specially engineered for use in agricultural equipment, engines, transmissions, and differentials with wet brake systems and integrated hydraulic systems. The carefully chosen base oils and additive system form a thermal and oxidation stable oil film thus keeping the engine, gearbox, differential, and hydraulic system clean and in good condition.

### APPLICATION:

Farmol oil is suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

### FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

### PERFORMANCE LEVELS: Meets and Exceeds:

- API: CG-4 / GL-4
- ZF TE-ML 06A, B, C, R, 07B
- FORD M2C 159B, C
- FORD NH 82009201, 2, 3
- FORD M2C 86B, C, 134D
- MASSEY FERGUSON M1145, M1139, M1144
- JOHN DEERE JDM J27, J20C, J20D
- ALLISON C4 • Suitable for Wet Bakes

### TYPICAL PROPERTIES:

| PARAMETERS                         | ASTM   | UNIT  | AGROL STOU |        |
|------------------------------------|--------|-------|------------|--------|
|                                    |        |       | 10W-30     | 20W-40 |
| Grade                              |        |       | 10W-30     | 20W-40 |
| Kinematic Viscosity @ 104°F /40°C  | D-7042 | cSt   | TBR        | TBR    |
| Kinematic Viscosity @ 212°F /100°C | D-7042 | cSt   | 11.6       | 14.9   |
| Viscosity Index                    | D-2270 | -     | 152        | 128    |
| Density @15°C/ 60°F                | D-4052 | g/cm3 | TBR        | TBR    |
| Flash Point (min)                  | D-92   | °C    | 226        | 236    |
| Pour Point (max)                   | D-97   | °C    | -39        | -24    |

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.