



AGROL UTTO MINERAL

PRODUCT DESCRIPTION:

Agrol Utto is a premium quality multipurpose tractor lubricant designed to meet or exceed transmission and hydraulic fluid requirements. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter. It helps protect against wear and corrosion of tractor components and has excellent anti-friction properties. Agrol Utto optimises the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

APPLICATION:

Farmol oil is suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

PERFORMANCE LEVELS: Meets and Exceeds:

- API GL-4
- ALLISON C4
- Case MS 1204,6,7,9
- Caterpillar TO-2
- Ford / NewHolland FNHA-2-C-201.00
- Ford M2C-48B/C
- Ford M2C-159A
- Ford M2C-86B/C - Ford M2C-134 A/B/C/D
- New Holland NH 410B
- John Deere J20 A/B/C, J14 B/C
- Massey Ferguson M1135, M1141, M1143, M 1145
- ZF TE-ML-03E, 05F, 06K

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	AGROL UTTO
Grade			10W-30
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.6
Viscosity Index	D-2270	-	152
Density @15°C/ 60°F	D-4052	g/cm3	TBR
Flash Point (min)	D-92	°C	226
Pour Point (max)	D-97	°C	-39

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.