



AVENO LA MINERAL

PRODUCT DESCRIPTION:

Aveno LA is a high-quality, heavy-duty, & selected two-stroke low-ash crankcase oil specifically blended to lubricate a wide range of four-stroke natural gas and dual-fuel engines where low-ash oils are recommended. It is engineered with premium quality base oils and additive technology to provide exceptional oxidation and nitration resistance, extended oil and filter life, and outstanding wear protection.

APPLICATION:

- Gas-fueled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended
- Naturally aspirated and turbo-charged gasoline engines in passenger cars where API SM or lower performance oils are specified
- Light truck gasoline engines where API SM or lower performance oils are specified
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils of API SM or lower performance

FEATURES & BENEFITS:

- Special detergent and ashless dispersant additive system preserve power and performance by providing good control of piston and ring deposits, even under high temperature conditions
- Good nitration resistance protects against CNG related valve deposits
- Very good thermal and oxidation stability
- Single oil for fleet owners with CNG, dual-fuel and gasoline vehicles

PERFORMANCE LEVELS: Meets and Exceeds:

- | | | |
|--|---|--|
| <ul style="list-style-type: none"> • Caterpillar • Wärtsilä • MAN • MTU • GE - Jenbacher • MWM (DEUTZ) | <ul style="list-style-type: none"> • Waukesha • Perkins • MDE • MTU • Superior STGV • Jenbacher | <ul style="list-style-type: none"> • Cummins • Hyundai • API CF (Diesel Fuel Application) |
|--|---|--|

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	AVENO LA	
SAE Grade			30	40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.50	15.20
Viscosity Index	ASTM D-2270	-	100	106
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR	TBR
Flash Point (min)	ASTM D-92	°C	242	256
Pour Point (max)	ASTM D-97	°C	-15	-15
TBN	ASTM D-2896	Mg KOH/g	5.6	5.6
Sulphatd Ash	ASTM D-871	Wt.%	0.5	0.5

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.