



## AVENO PRO MINERAL

### PRODUCT DESCRIPTION:

Aveno Pro is engineered to provide faster and cleaner engine protection to make sure of longer engine life. It is blended for use in gas-fueled engines in passenger cars and light commercial vehicles. It has a special additive system that resists wearing under all operating conditions by forming a protective layer on contact surfaces. The high viscosity index provides additional protection against wear at start-up and under high-temperature operating conditions.

### APPLICATION:

- Gas-fueled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended
- Naturally aspirated and turbo-charged gasoline engines in passenger cars where API SM or lower performance oils are specified
- Light truck gasoline engines where API SM or lower performance oils are specified
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger cars motor oils of API SM or lower performance

### FEATURES & BENEFITS:

- Special detergent and ashless dispersant additive system preserve power and performance by providing good control of piston and ring deposits, even under high temperature conditions.
- Good nitration resistance protects against CNG related valve deposits
- Very good thermal and oxidation stability
- Single oil for fleet owners with CNG, dual-fuel and gasoline vehicles

### PERFORMANCE LEVELS: Meets and Exceeds:

- API SM
- Suitable for use also where API SL, SJ or SG oils are specified

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	AVENO PRO
Grade			20W50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	19
Viscosity Index	ASTM D-2270	-	127
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	240
Pour Point (max)	ASTM D-97	°C	-27
TBN	ASTM D-2896	Mg KOH/g	8
CCS, (°C)	ASTM D-5293	m.Pa.S	8900 (-15)

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.