



## DYNA PLUS

HIGH-PERFORMANCE ATF WITH REDUCED VISCOSITY FOR BETTER FUEL EFFICIENCY.

### PRODUCT DESCRIPTION:

Dyna Plus is a premium quality ATF with reduced viscosity based on the most advanced additives and a special base oil stock composition made of HC synthetic oils and fully synthetic poly-alpha-olefins (PAO). Developed specifically for use in modern 6/8/9-speed automatic transmissions in SUV, mid-size, and luxury vehicles.

### APPLICATION:

Dyna Plus has been adapted to the special requirements of modern 6/8/9-speed automatic transmissions in high-performance SUV and vehicles from the upper mid-range and luxury class. Its specific friction coefficient level ensures the slip-free transmission of very high torques, thus making spontaneous and sporty shifting operations possible without compromising comfort. In so doing, its excellent friction coefficient stability guarantees unvarying shifting performance over the entire service interval.

### FEATURES & BENEFITS:

- Adapted friction coefficient behavior for spontaneous and sporty shifting operations
- Prevention of friction vibrations in a reliable manner, thus providing maximum comfort
- Excellent friction coefficient stability over the entire service interval
- Reduced viscosity for better fuel efficiency
- Excellent shifting characteristics at low temperatures
- The best wear protection properties for reliable operation and the longest service life
- Highest oxidation and ageing stability due to a special base oil composition made of HC synthetic and fully synthetic PAO base oils
- Minimal tendency to foam
- Reliable protection against corrosion, wear, sludge accumulation and adhesion
- Neutral behavior towards gasket materials
- Miscible and compatible with other ATF of the same specification. However, in order to exploit the full product benefits of HIGHTEC ATF 9008, a complete oil change is strongly recommended.

### PERFORMANCE LEVELS: Meets and Exceeds:

- Chrysler 68157995AA
- BMW 83 22 2 152 426/83 22 2 305 397 (BMW L12108)/83
- 22 2 289 720 (ATF3+)
- Fiat 9.55550-AV5
- Honda ATF-Type 3.1
- Jaguar 02JDE 26444
- Land Rover LR023288
- VW G 060 162/G 055 540
- ZF 5671 090 312

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DYNA PLUS
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /1000C	ASTM D-7042	cSt	7.25
Viscosity Index	ASTM D-2270	-	180
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	200
Pour Point (max)	ASTM D-97	°C	-42

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.