



DYNADEX 3 SYNTHETIC

PRODUCT DESCRIPTION:

Dynadex 3 is a high-performance fully synthetic automatic transmission fluid blended with premium, severely hydro-processed base stocks and additives that help provide oxidation and thermal stability, friction control, load-carrying ability, corrosion, and wear protection. It helps protect against the formation of deposits, sludge, varnish, and foam and provides outstanding durability.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, heavy-duty automatic transmissions, power steering units and hydraulic systems requiring Dexron III G and Allison C-4 fluids.

FEATURES & BENEFITS:

- It provides protection against the formation of lacquers, sludge or other harmful deposits
- Exceptional stability provided by excellent base oil and extra oxidation inhibitors
- Especially effective in minimizing transmission "chatter." Helps ensure smooth, quiet action at all speeds
- It ensures fast circulation during cold weather and excellent lubrication when hot

PERFORMANCE LEVELS: Meets and Exceeds:

- GM DEXRON III, IIIH
- ZF TE-ML 14A, 03D, 04D, 17C, 09C
- VOITH H55.6335.xx
- VOITH 55.6336.3x
- MAN 339 TYPE V1/Z1/V2/Z2
- MB 236.9/236.1/236.5/236.6/236.10
- ALLISON TES-389
- VOLVO 97340, 97341
- FORD M, FORD TASA
- ALLISON C4

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DYNADEX 3
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /1000C	ASTM D-7042	cSt	7.25
Viscosity Index	ASTM D-2270	-	180
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	200
Pour Point (max)	ASTM D-97	°C	-42

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.