



## DYNATEC 4 SYNTHETIC

### PRODUCT DESCRIPTION:

Dynatec 4 automatic transmission fluid is engineered for use in most types of Japanese, Korean, and Chrysler vehicles that require ATF+4 or prior specifications. This product offers excellent low temperature and improved anti-shudder properties. Dynatec 4 is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese, and other manufacturers from around the world specifying Chrysler ATF+4, ATF+3, or ATF+2 type fluids.

### FEATURES & BENEFITS:

- Excellent flow properties at low start-up temperatures and high operating temperatures
- Improved shift performance and vehicle drivability/improved shudder performance
- Good viscosity stability
- Excellent oxidation stability, less fluid breakdown in high-temperature service
- Dependable protection against rust and corrosion
- Provides more assured wear protection for maximum transmission/transaxle life
- Engineered with superior base oils to ensure superb low and high temperature performance

### APPLICATION:

- Automatic transmissions specially formulated for Chrysler vehicles, including Dodge, Plymouth, Eagle and certain Jeeps, that require a fluid meeting ATF+4 specification.
- Mitsubishi and Hyundai applications where an MS-9602 type fluid is specified.
- Services that specify an ATF+, ATF+2 and ATF+3 type fluid, including certain manual transmissions, transfer cases and power steering units (1999 and later).

### PERFORMANCE LEVELS: Meets and Exceeds:

- Chrysler ATF+4® Requirements
- Chrysler MS-9602

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DYNATEC 4
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7.30
Viscosity Index	ASTM D-2270	-	205
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	198
Pour Point (max)	ASTM D-97	v°C	-51
Viscosity Brookfield @ -40 °C	ASTM D2983	mPa.s (cP)	8400

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venöm retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.