



## DYNATEC 6HP AUTOMATIC TRANSMISSION FLUID

### PRODUCT DESCRIPTION:

Dynatec 6HP is an Automatic Transmission Fluid (ATF) suitable for a large variety of applications. It is formulated from selected synthetic base oils and special additives which guarantees a perfect function of the automatic transmission and offers safe operation even under high stress.

### APPLICATION:

Dynatec 6HP fluid is developed for use in the 6HP-series transmission of ZF 6HP19, 6HP21, 6HP26, 6HP28, 6HP32, 6HP34 and also for 5 speed automatic transmission 5HP-series. It is backwardly compatible with all earlier versions of ZF 4 and 5 gear passenger cars' automatic transmission.

### FEATURES & BENEFITS:

- Excellent lubricating ability even at very low temperatures.
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Neutral towards sealing materials
- Optimum power transmission ability

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- BMW ATF M 1375.4 (8322 0142516)
- Bentley Oil PY112995PA
- FORD MERCOR SP/LV
- Hyundai SP-IV
- Jaguar Fluid 8432
- Land Rover TYK 500050
- Maserati Oil 231603
- Nissan Matic S
- Toyota Type WS
- VW / Audi G 055 005 A1/A2/A6
- ZF Lifeguardfluid6 (S671 090 255)
- FORD WSS- M2C 8432
- BMW ATF2
- JAGUAR C2C 8432
- ZF S671 090 252/253

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	DYNATEC 6HP
KV @ 104°F / 40°C	D7042	cSt	TBR
KV @ 212°F / 100°C	D7042	cSt	6.1
Viscosity Index	D2270	-	155
Density @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.