



DYNATEC CHF - CENTRAL HYDRAULIC FLUID

PRODUCT DESCRIPTION:

Dynatec CHF is a high-performance multi-purpose synthetic hydraulic fluid with ashless additives. It is specially blended for power steering, brake, suspension leveling, and hydraulic suspension systems of modern cars. It can also be used in shock absorbers, hydro-pneumatic suspension, traction, and stability control systems.

APPLICATION:

Dynatec CHF is recommended for the service re-fill or top-up of the power steering and suspension systems in many late model European manufactured prestige vehicles. It can also be used as a direct replacement for OEM LDS fluids or it is a ready replacement for OEM Pentosin CHF 11S and can also be used as a replacement for LHM+ type fluids creating less inventory for workshops. Dynatec CHF may also be used in the brake systems of certain vehicles, please check the vehicle handbook before use.

FEATURES & BENEFITS

- Good flow rates of fluid at extremes of temperature
- Excellent lubricating properties
- High thermal stability
- Excellent protection against wear & corrosion
- Excellent compatibility with all kind of seals and hoses

TYPICAL PERFORMANCE:

PARAMETERS	DYNATEC CHF (Typical Specification)
MAN	M3289
MB	345.0
PENTOSIN	CHF 11S
Chrysler	MS-11655
FORD	M2C204-A
BMW	81 22 9 407 758
VW/SEAT/SKODA/AUDI	G 002 000 (TL 521 46), G 004 000
HYUNDAI/KIA	PSF-3/PSF-4
FIAT	9.55550-AG2/9.55550-AG3 VG 22
GM	89021185/ 89021186/ 1052884/ 993294
VOLVO	1161529

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venöm retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.