



## DYNATEC CVT SYNTHETIC

### PRODUCT DESCRIPTION:

Dynatec CVT is an advanced fully synthetic high performance multi-vehicle transmission fluid for passenger cars and vans. A well-balanced fluid that provides exceptional metal-to-metal frictional properties to help prevent belt and chain slipping and help extend transmission life. It provides superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration, and harshness.

### APPLICATION:

Especially recommended for use in push belt and chain-driven continuously variable transmissions of most European, Asian, and American passenger cars and vans.

### FEATURES & BENEFITS:

- Exceptional steel on steel friction durability maintains transmission performance
- Good gear wear protection prolongs the performance and life of the transmission
- High shear stability and enhanced anti foaming and air release characteristics maintain effective lubrication
- Superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness
- In elevated heat, guards against the harmful effects of thermal breakdown

### PERFORMANCE LEVELS: Meets and Exceeds:

- Mazda CVTF 3320
- MB 236.2
- Nissan NS-1, NS-2, NS-3
- Toyota/Lexus TC, FE
- Ford CVT23, CVT30, WSS-M2C933-A
- Mitsubishi DiaQueen CVTF-J1/CVTF-J4/SP-III
- Audi/VW TL 52180, G 052 180, G 052 516
- Suzuki CVTF 3320, TC, NS-2, CVTF Green1, CVTF Green 2
- Honda HMMF / HCF-2 / Z1
- AUDI MULTITRONIC
- BMW MINI COOPER EZL799/799A/ZF CVT V1
- DAIHATSU AMMIX DC/DFC/CVTF-DFE
- DAIHATSU TC
- CHRYSLER/DODGE/JEEP NS-2/CVT +4
- GM DEX-CVT
- HYUNDAI/KIA CVT-J1 / SP-III
- IDEMITSU CVTS-EX1
- VAG TL 521 16 (G052 516) / TL 521 80 (G 052 180 A2)
- PUNCH CVT
- SHELL GREEN 1V
- SUBARU ECVT / iCVT / iCVT FG / NS2 / LINEARTRONIC CVT CHAIN / LINEARTRONIC CVT II / HIGH TORQUE LINEARTRONIC

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DYNATEC CVT
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7
Viscosity Index	ASTM D-2270	-	173
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	220
Pour Point (max)	ASTM D-97	°C	-45
Brookfield Viscosity @ -40 °C	ASTM D-2983	°C	9000

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.