



DYNATRONIC

9 SPEED AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

Dynatronic is a high-performance Automatic Transmission Fluid (ATF) formulated with latest technology synthetic base oils combined with premium quality performance additives. It's a service fill fluid for the latest generation of fuel economy optimized 9 speed automatic transmissions.

APPLICATION:

Dynatronic is recommended for the latest generation of Mercedes-Benz 9-speed automatic transmissions (9G-tronic).

FEATURES & BENEFITS

- High thermal and oxidative stability.
- Improved lubricating
- Outstanding shear stability
- maximum reduction of fuel consumption, which reduces emission
- Superior overall performance

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

MB 236.17

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	DYNATRONIC
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	4.2
Viscosity Index	D2270	-	138
Density @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-45

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.