



INERTIA 3

PRODUCT DESCRIPTION:

Inertia 3 is a DOT 3 brake fluid based on polyglycol and is engineered for use in the hydraulic brake system of commercial vehicles, passenger cars, and motorcycles operating under moderate service conditions and requiring a DOT 3 type of fluid. It also is compatible with all seals and metals used in conventional braking systems. It provides lubrication and system protection. It also is compatible with all seals and metals used in conventional braking systems.

APPLICATION:

Inertia 3 is a high-performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems.

FEATURES & BENEFITS

- Superior oxidative stability
- High boiling point
- Excellent low temperature fluidity ensure trouble free operation
- Effective corrosion inhibitors provide Improved life and reliability of brake system components\

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- FMVSS 116 DOT 3
- SAE J1703
- ISO 4925 Class 3

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	INERTIA 3
Kinematic Viscosity @ -40C	D-445	°C	TBR
Kinematic Viscosity @ 100C	D-445	-	> 1.5
Density @15°C	D-1298	g/cm3	TBR
DRY ERBP	D-1120	°C	> 205
WET ERBP	D-1120	°C	> 140
pH	D-1287	°C	7 to 11.5

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.