

INERTIA 4 LV

PRODUCT DESCRIPTION:

Inertia 4 LV is a very high-performance Brake and Clutch Fluid that conforms to the latest ISO 4925 Class 6 standard. The high wet boiling point of Inertia 4 LV as compared to conventional DOT 4 enables a longer product lifetime. Its exceptional low-temperature viscosity allows easier fluid circulation in micro-valves of anti-locking systems for the better response of ABS, ESP, and ASR high-pressure systems.

APPLICATION:

Inertia 4 LV brake fluid can be used in all vehicles where ISO 4925 Class 6 specification is required. It is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ABS (Anti-lock Braking System), ESP (Electronic Stability Program) and ASR (Acceleration Slip Regulation). Inertia 4 LV is mixable with DOT 3, DOT 4 and DOT 5.1 NON-SILICONE BASE products. Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

FEATURES & BENEFITS

- Optimal ABS properties.
- Exception chemical stability.
- High lubricating power.
- Exceptional low viscosity at low temperature.
- Higher Dry and Wet boiling points.
- Miscibility with all brake fluids of the same specification.

TYPICAL PERFORMANCE:

PARAMETERS	INERTIA 4 LV
ISO	4925 Class 6
FMVSS 116	DOT 4
SAE	J 1704
MB	331.0
VW	501.14 (TL 766-Z)
FORD	WSS-M6C65-A2/M6C57-A2
BMW	QV 34001

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.