





INERTIA-4 SUPER BLUE HIGH-PERFORMANCE BRAKE FLUID

PRODUCT DESCRIPTION:

Inertia-4 Super Blue is a very high boiling point (280°C) brake fluid. The overall high dry and wet boiling points make this fluid an excellent choice for street-driven vehicles, too, where brake fluid is flushed less frequently than that in race-driven vehicles. The advanced formulation offers a minimal drop in boiling point due to outstanding water-binding properties resulting in a long-lasting fluid that may not need to be changed for up to 3 years under normal highway driving conditions.

APPLICATION:

Inertia-4 Super Blue is designed to excel within the extreme demands made on a race vehicle or by high performance drivers and exceeds all DOT4 standards. It is compatible with and will mix well with most DOT3, DOT4 or DOT 5.1 fluids.

FEATURES & BENEFITS:

- · High dry boiling point
- · High wet boiling point
- · High lubricating power
- · Exceptional low viscosity at low temperature
- · Miscibility with all brake fluids of the same specification

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- ISO 4925 Class 6
- FMVSS 116 DOT 4
- SAE J 1704

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	INERTIA-4 SUPER BLUE
Kinematic Viscosity @100C	D445	cSt	2.1
Kinematic Viscosity @-40C	D445	cSt	TBR
Boiling Point (Reflux)	D1120	°C	280
Wet Boiling Point	D1120	°C	198
Density at 15℃	D4052	g/ml	TBR

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.