



SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name: HYDOL EAL HYDRAULIC OIL VG 100
Product Type: Liquid

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance / Mixture: Hydraulic Oils
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the Supplier of the Safety Data Sheet

Supplier: REXOL FZC, PO Box 52341, Plot 1F-09B, 09B
Hamriyah Free Zone, Sharjah, United Arab Emirates

Supplier Phone & Email Address: Phone: +971 6 561 8895 Email: info@venomoil.de
Date of Issue: 01-DEC-2021
Date of Revision: 01-JUL-2022
Prepared by: REXOL FZC

1.4 Emergency Telephone Number

Emergency Telephone Number: United Arab Emirates, Government of Sharjah, Hamriyah Free Zone
Authority, SAFETY PH NO. +971 6 526 1666 (24x7)
EMERGENCY PH NO. +971 6 526 2111 (24x7)

SECTION 2: Hazard Identification

2.1 Classification of the Substance / Mixture

Product Definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]: Not Classified

Classification according to Directive 1999/45/EC [DPD]: The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.
See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label Elements



| | |
|---|---|
| Signal Word: | No signal words. |
| Hazard Statements: | No known significant effects or critical hazards. |
| Precautionary Statements: | |
| Prevention | Not applicable. |
| Response | Not applicable. |
| Storage | Not applicable. |
| Disposal | Not applicable. |
| Supplemental Label Elements: | Not applicable. |
| Special Packaging Requirements: | |
| Containers to be fitted with child-resistant fastenings | Not applicable. |
| Tactile Warning of Danger: | Not applicable. |

2.3 Other Hazards

| | |
|--|--|
| Other Hazards which do not Result in Classification: | Defatting to the skin. USED HYDRAULIC OILS Used HYDRAULIC OIL may contain hazardous components, which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet. |
|--|--|

SECTION 3: Composition/Information on Ingredients

| | |
|----------------------|---|
| Substance / Mixture: | Mixture Highly refined base oil (IP 346 DMSO extract < 3%). Chemically modified base oil and Proprietary performance additives. This product does not contain any hazardous ingredients at or above regulated thresholds. |
|----------------------|---|

SECTION 4: First Aid Measures

4.1 Description of First Aid Measures

| | |
|---------------|--|
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. |
| Eye Contact: | Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention. |
| Skin Contact: | Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops. |
| Ingestion: | Do not induce vomiting unless directed to do so by medical personnel. Get |



| | |
|-----------------------------|--|
| Inhalation: | medical attention if Symptoms occur. |
| | If inhaled, remove to fresh air. Get medical attention if symptoms appear. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Protection of First Aiders: | No action shall be taken involving any personal risk or without suitable training. |

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of Immediate Medical Attention and Special Treatment Needed

| | |
|---------------------|--|
| Notes to Physician: | See Section 11 for more detailed information on health effects and symptoms. |
|---------------------|--|

SECTION 5: Fire Fighting Measures

5.1 Extinguishing Media

| | |
|--------------------------------|--|
| Suitable Extinguishing Media | In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray. |
| Unsuitable Extinguishing Media | Do not use water jet. |

5.2 Special Hazards Arising from Substance / Mixture

| | |
|---------------------------------------|---|
| Hazards from the Substance or Mixture | In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous Combustion Products | Combustion products may include the following: Carbon Oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) |

5.3 Advice for Fire Fighters

| | |
|--|---|
| Special precautions for fire-fighters | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, |



protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|--|
| For non-emergency personnel | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment. |
| For emergency responders | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel". |

6.2 Environmental Precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and Material for Containment and Cleaning Up

| | |
|-------------|--|
| Small Spill | Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large Spill | Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, watercourses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. |

6.4 Reference to Other Sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and Storage



7.1 Precautions for safe handling

| | |
|--|---|
| Protective measures | Put on appropriate personal protective equipment. |
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabeled containers.

7.3 Specific and End Use(s) Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure Controls / Personal Protection

8.1 Control Parameters

| | |
|-----------------------------------|--|
| Occupational Exposure Limits | No exposure limit value known measures. Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only. |
| Recommended Monitoring Procedures | If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of |



chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level No DNELs/DMELs available

Predicted No Effect Concentration No PNECs available.

8.2 Exposure Controls

Appropriate Engineering Controls Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organization for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures
Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory Measures Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye / Self Protection Safety glasses with side shades

Skin Protection

Hand Protection General Information:
Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after



repeated chemical exposures). Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile Gloves

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are considered. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes must be determined and rigorously followed.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks.

For Example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and Body:

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to Standards

Respiratory protection: EN529



Gloves: EN420, EN374

Eye protection: EN166

Environmental Exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

| | |
|--|---|
| Appearance | |
| Physical State | Liquid |
| Color | Light Amber |
| Odor | Typical Petroleum |
| Odor threshold | Not Available |
| pH | Not Available |
| Melting point/freezing point | Not Available |
| Initial boiling point and boiling range | Not Available |
| Pour point | -40 °C |
| Flash point | 286 °C |
| Evaporation rate | Not Available |
| Flammability (solid, gas) | Not Available |
| Upper/lower flammability or explosive limits | Not Available |
| Vapor pressure | Not Available |
| Vapor density | Not Available |
| Relative density | Not Available |
| SP. Gravity @15°C/ 60°F | 0.93 g/cm ³ |
| Solubility | Insoluble in water. |
| Partition coefficient: | Not Available |
| Auto-ignition temperature | Not Available |
| Decomposition temperature | Not Available |
| Viscosity | Kinematic Viscosity 14.5 cSt @ 212°F /100°C |
| Explosive properties | Not Available |
| Oxidizing properties | Not Available |

9.2 Other Information

No Additional Information

SECTION 10: Stability and Reactivity

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to



avoid and Incompatible materials for additional information.

10.2 Chemical Stability

This product is stable.

10.3 Possibility of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

10.4 Conditions to Avoid

Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible Materials

Reactive or incompatible with Oxidizing Materials

10.6 Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

11.2 Information on Toxicological Effects

| Acute Toxicity Estimates | Route | ATE Value |
|--|------------------------------|--------------|
| Petroleum derived calcium salt 61789-86-4 | Oral | > 5000mg/kg |
| | Dermal | > 4000 mg/kg |
| | Inhalation (dusts and mists) | 418.6 mg/l |

Information on the likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

| Potential Acute Health Effects | |
|--------------------------------|--|
| Inhalation | Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. |
| Ingestion | No known significant effects or critical hazards. |
| Skin Contact | Defatting to the skin. May cause skin dryness and irritation. |



Eye Contact

No known significant effects or critical hazards.

No specific data

No specific data

Adverse symptoms may include irritation, dryness, cracking

No specific data

Over exposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion of large quantities may cause nausea and diarrhea. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Potential risk of transient stinging or redness if accidental eye contact occurs.

Used Hydraulic Oils:
Used HYDRAULIC OIL may contain hazardous components, which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used HYDRAULIC OIL must therefore be avoided and a high standard of personal hygiene maintained.

No know significant effects or critical hazards.

No know significant effects or critical hazards.

No know significant effects or critical hazards.

No know significant effects or critical hazards.

SECTION 12: Ecological Information

12.1 Toxicity

Environmental Hazard

Not classified as dangerous.

12.2 Persistence and Degradability

Partially biodegradable.



12.3 Bio Accumulative Potential

This product is not expected to bio accumulate through food chains in the environment.

12.4 Mobility in Soil

Soil / Water partition coefficient (KOC) Not available

Mobility Spillages may penetrate the soil causing ground water contamination

12.5 Result of PBT and vPVB Assessment

PBT Not applicable

vPVB Not applicable

12.6 Other Adverse Effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13: Disposal Considerations

13.1 Waste Treatment Methods

Methods of Disposal Where possible, arrange for product to be recycled. Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.

Waste Code

13 02 08*

Waste Designation

Other transmission, engine, gear, hydraulic and lubricating oils

However, deviation from the intended use and/or the presence of a potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packing

Methods of Disposal

Where possible, arrange for product to be recycled. Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.

Special Precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.



SECTION 14: Transport Information

| | ADR/RID | ADN | IMDG | IATA |
|-----------------------------------|---------------|---------------|---------------|---------------|
| 14.1 UN Number | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.2 UN Proper Shipping Name | - | - | - | - |
| 14.3 Transport Hazard Class | - | - | - | - |
| 14.4 Packing Group | - | - | - | - |
| 14.5 Environmental Hazards | NO | No | No | No |
| Additional Information | - | - | - | - |
| 14.6 Special Precautions for User | Not available | | | |

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

None of the components are listed

Substances of very high concern

Not applicable

Annex XVII - Restrictions on the manufacturer, placing on the market and use of certain dangerous substances, mixtures and articles.

Other Regulations

REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States Inventory (TSCA 8b)

All components are listed or exempted.

Australia Inventory (AICS)

At least one component is not listed.

Canada Inventory

At least one component is not listed.

China Inventory (IECSC)

At least one component is not listed.

Japan Inventory (ENCS)

At least one component is not listed.

Korea Inventory (KECI)

At least one component is not listed.

Philippines Inventory (PICCS)

At least one component is not listed.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.



SECTION 16: Other Information

Abbreviations and Acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bio Concentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labeling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 DPD = Dangerous Preparations Directive [1999/45/EC]
 DSD = Dangerous Substances Directive [67/548/EEC]
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labeling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organization for Economic Co-operation and Development
 PBT = Persistent, Bio Accumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bio Accumulative

| | | |
|--|---|--|
| Full text of abbreviated H statements | H 304 | May be fatal if swallowed and enters airways. |
| Full text of classifications [CLP/GHS] | H 413 Aquatic Chronic 4, H413 Asp. Tox. 1, H304 | May cause long lasting harmful effects to aquatic life. LONG-TERM AQUATIC HAZARD - Category 4 ASPIRATION HAZARD - Category 1 |
| Full text of abbreviated R Phrases | R53- | May cause long-term adverse effects in the aquatic environment. |
| Full text of classifications [DSD/DPD] | Not Applicable | |

History

Date of Issue 01-DEC-2021



Date of Revision

01-JUL-2022

Prepared by

REXOL FZC

Notice to Reader:

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from REXOL FZC. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The REXOL FZC shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the REXOL FZC to ensure that this document is the most current available. Alteration of this document is strictly prohibited.