



## RIDER 9000

### SYNTHETIC / SEMI SYNTHETIC / MINERAL

#### PRODUCT DESCRIPTION:

Rider 9000 is recommended for high-performance 4T motorcycles that deliver high power efficiency and acceleration. Rider 9000 is excellent in maintaining high engine power and fuel economy with longer drain intervals. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions.

#### APPLICATION:

Recommended for all scooters and motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

#### FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

#### PERFORMANCE LEVELS: Meets and Exceeds:

- API SL
- JASO MA2

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	RIDER 9000					
			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50
Grade			TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	14.6	11.9	14.4	25.3	15.2	20.4
Viscosity Index	ASTM D-2270	-	164	150	156	170	126	129
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D-92	°C	230	226	228	230	236	236
Pour Point (max)	ASTM D-97	°C	-36	-36	-36	-36	-24	-24
TBN	ASTM D-2896	Mg KOH/g	6	6	6	6	6	6
CCS, (°C)	ASTM D-5293	m.Pa.S	6600 (-30)	6850 (-25)	6750 (-25)	6800 (-25)	9100 (-15)	9200 (-15)

#### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

#### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

#### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

#### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.