



SPIRAL HYPOID G2

AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

Spiral Hypoid G2 is an advanced fully synthetic axle lubricant made from premium quality base oils and a high-performance additives system that ensures exact friction behavior and provides outstanding aging resistance. It is a performance-optimized front-axle transmission oil that has been specially developed for front-wheel drive gearboxes. It reduces torque loss and improves the efficiency of the axle drive.

APPLICATION:

Spiral Hypoid G2 is specially designed oil for the high demands of BMW front axle transmission. It reduces torque loss and improves the efficiency of the axle drive. The operating instructions of the vehicle and transmission manufacturers must be followed.

FEATURES & BENEFITS:

- Excellent viscosity/temperature properties
- Reduces running noise
- Outstanding corrosion protection
- Excellent wear resistance
- Very compatible with seals
- High pressure-absorption capability
- For extended oil-change intervals
- Excellent resistance to aging

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API GL-5
- BMW 83-22-2-413-511

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SPIRAL HYPOID G2
			75W-85
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	12.0
Viscosity Index	D2270	-	171
Density @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.