

AUTOMOTIVE GEAR OIL

Technical Data Sheet



SPIRAL MAX 2330 MANUAL TRANSMISSION OIL

PRODUCT DESCRIPTION:

Spiral Max 2330 is a high-guality transmission oil, suitable for nearly all manual gear boxes of passenger cars. It is specially recommended for PSA manual gear boxes with extended drain interval and friction modifier additive adapted to PSA manual gear boxes.

APPLICATION:

•

Spiral Max is tested under strict conditions, this oil meets the general performance requirements of most brands and models in all weather conditions.

FEATURES & BENEFITS:

Smooth gear shifting. • Significantly extended transmission life

- · Provides good protection against wear and corrosion
- Reduced cost of maintenance due to long drain intervals

High resistance to oil degradation

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	75W-80		
API	GL-4		
PSA	B71 2330		
PSA	9730 A8		
MB	235.10		
FORD	WSD-M2C200-D		
FORD	ESD-M2C186-A		
GM	1940182		
GM	1940768		
HONDA	MTF 94		
VOLVO	97308/97309/97310		
NISSAN	MT-XZ		

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SPIRAL MAX 2330
			75W-80
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	9.1
Viscosity Index	D2270	-	150
Density @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	214
Pour Point (max)	D97	°C	-42
Brookfield Viscosity	D2983	ср	142,000(-40C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water,

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.