



## SPIRAL SYNTH EP 75W-90 EXTREME PRESSURE AUTOMOTIVE GEAR OIL

### PRODUCT DESCRIPTION:

Spiral Synth EP 75W-90 is a fully synthetic lubricant used for drive axles on General Motors vehicles where oil to GM specifications 9986115 is required.

### APPLICATION:

Spiral Synth EP 75W-90 is recommended as service-fill lubricant for drive axles on General Motors vehicles requiring the product meeting GM 9986115 specifications.

### FEATURES & BENEFITS

- Excellent viscosity/temperature properties
- Outstanding axle wear protection.
- outstanding corrosion protection
- excellent wear resistance
- Improved shear stability for a stable viscosity during use
- excellent resistance to aging

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- GM 9986115

### TYPICAL PERFORMANCE:

| PARAMETERS        | ASTM  | UNIT  | 75W-90 |
|-------------------|-------|-------|--------|
| KV@ 104°F /40°C   | D7042 | cSt   | TBR    |
| KV @ 212°F /100°C | D7042 | cSt   | 14.6   |
| Viscosity Index   | D2270 | -     | 160    |
| Density @15°C     | D4052 | g/cm3 | TBR    |
| Flash Point (min) | D92   | °C    | 200    |
| Pour Point (max)  | D97   | °C    | -45    |

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.