



## SPIRAL TRANSMAX EXTREME PRESSURE AUTOMOTIVE GEAR OIL

### PRODUCT DESCRIPTION:

Spiral Transmax is a multipurpose axle oil that may be used in differentials, final drives, and other applications in passenger cars and commercial vehicles where API GL-5 performance is required. It is a superior sulfur-phosphorus, extreme pressure gear lubricant formulated with high-performance base stocks, friction modifiers, and corrosion inhibitors, meeting the requirements of API GL-5 as well as many other manufacturer specifications. These oils are formulated to produce a superior gear lubricant with extreme pressure characteristics and thermal stability for automotive applications over a wide range of temperatures and heavy-duty conditions.

### APPLICATION:

Spiral Transmax oils are mainly recommended for use in spiral bevel and hypoid differentials, power dividers and transmissions requiring EP gear lubes under high speed, high load, high torque and high horse power conditions. Spiral Transmax meets or exceeds the quality requirements of numerous vehicle manufacturers such as IVECO, MAN, SCANIA and VOLVO for heavy vehicles rear axles and final drive units.

### FEATURES & BENEFITS:

- Extreme pressure properties protect hypoid and other types of gears from scuffing and wear.
- Superior thermal and oxidative stability
- High safety margin against foaming and corrosion
- Protects against oil seal deterioration

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	90	140	80W-90	85W-90	80W-140	85W-140	75W-90
API	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5
MIL	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D
MAN	342 M2	-	342 M2	342 M2	-	-	342 M2
ZF	12E/16B 16C/17B 19B/21A	16D	12E/16B 16C/17B 19B/21A	12E/16B 16C/17B 19B/21A	12E/16C 16D/21A	12E/16C 16D/21A	12E/16B16C 17B/21A

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SPIRAL TRANSMAX						
			90	140	80W-90	85W-90	80W-140	85W-140	75W-90
KV@ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
KV @ 212°F /100°C	D7042	cSt	17.5	28.3	15.6	17.5	28.5	28.2	14.4
Viscosity Index	D2270	-	96	97	114	96	165	96	174
Density @15°C	D4052	g/cm3	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	230	236	220	230	218	234	214
Pour Point (max)	D97	°C	-9	-9	-27	-15	-27	-12	-42
Brookfield Viscosity	D2983	cp	-	-	90,000 (-26C)	100,000 (-12C)	110,000 (-12C)	120,000 (-26C)	135000 (-40C)

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.