



SPIRAL V-PLUS

SYNTHETIC TRANSMISSION OIL

PRODUCT DESCRIPTION:

Spiral V-Plus is a premium performance fully synthetic transmission fluid with extended drain interval. It is designed for heavy- duty synchronized manual truck transmissions.

APPLICATION:

Spiral V-Plus is designed for heavy-duty synchronized manual truck transmissions requiring extended drain interval. It is also suitable for many OEMs like MAN, Mercedes Benz, Scania, transmissions manufactured by ZF, including AS Tronic models and models fitted with intertarders.

FEATURES & BENEFITS

- Long drain interval up to 450,000Km
- Outstanding cold flow properties
- Smooth shifting
- Improved fuel economy
- Improved shear stability for a stable viscosity during use
- Excellent resistance to corrosion, wear and aging

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	75W-80	75W-90
API	GL-4	GL-4
VOITH	Class C	-
VOLVO	97307/97318	97315/97319
MB	235.4/ 235.41/235.11	235.11
MAN	341 TYPE E4/Z4	-
ZF	TE-ML 02L	-

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SPIRAL V-Plus	
			75W-80	75W-90
KV@ 104°F /40°C	D7042	cSt	TBR	TBR
KV @ 212°F /100°C	D7042	cSt	10	17
Viscosity Index	D2270	-	151	165
Density @15°C	D4052	g/cm3	TBR	TBR
Flash Point (min)	D92	°C	210	210
Pour Point (max)	D97	°C	-45	-41

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.