



SPO MOLD RELEASE AGENT DEMOULDING OIL FOR CEMENT PRODUCTS

PRODUCT DESCRIPTION:

SPO Mold Release Agent is an extremely light demoulding oil for cement products. It prevents adhesion by developing a physical film or barrier between the forming surface and the concrete. It has been specially developed for concrete demoulding where the oil creates a layer between the concrete and the mould. This layer is a critical part of the process as the chemistry of the product will result in soap formations at the interface.

APPLICATION:

SPO Mold Release Agent is used for tiles, cement slates, fence posts and thin flat sections and other prefab elements of medium to higher quality.

FEATURES & BENEFITS:

- Superior quality of the surface
- Light colour
- Enriched with special additives
- Prevents sticking
- Extremely handy to apply

TYPICAL PROPERTIES:

PARAMETERS	METHOD	UNIT	TYPICAL
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	TBR
Kinematic Viscosity, 40 °C	D 445	mm ² /s	2.0
Flash Point, COC	D 92	°C	84
tv Test, Proc. A and B, 24 h	D 665	-	pass

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.