



SPO SHOCK ABSORBER OIL

PRODUCT DESCRIPTION:

SPO Shock Absorber Oil is formulated using high-performance base oils & combination of additives to provide excellent damping effect for shock absorbers used in motorcycles. This oil has excellent viscosity temperature behavior, oxidation stability & anti-foam properties. It has also a very good seal compatibility.

APPLICATION:

Recommended as hydraulic fluid for front fork motorcycles & other shock absorbers mechanism

FEATURES & BENEFITS:

- Increase the life of shock absorber
- Excellent seal compatibility
- Longer oil life
- Excellent damping effect
- Excellent low temperature properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SPO Shock Absorber Oil
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	5.4
Viscosity Index	ASTM D-2270		102
Flash Point (min)	ASTM D-92	°C	210
Pour Point	ASTM D-97	°C	-24

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.