



SWIFT C1 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift C1 5W-30 is the new generation low SAPS fully synthetic engine oil designed to meet the needs of latest engine technologies of gasoline and diesel engines fitted with after treatment systems. It offers excellent performances at both low and high operating temperatures and long-term engine protection. Swift C1 utilizes low SAPS technology which helps prolong the life and maintain the efficiency of after-treatment systems in both diesel and gasoline powered automobiles.

APPLICATION:

Swift C1 5W-30 is recommended for applications requiring Ford WSS-M2C934-B and Jaguar Land Rover STJLR.03.5005 which includes Jaguar and Land Rover vehicles from January 2009 fitted with the 3.0 Litre V6 Diesel engine, and Mazda Diesel engines fitted with Diesel Particulate Filter (DPF) from 2005 requiring an ACEA C1 oil with SAE 5W-30 viscosity grade.

FEATURES & BENEFITS:

- Low SAPS formula helps maintain efficiency of diesel particulate filters and catalytic converters.
- Provides engine cleanliness and improved engine efficiency.
- Unsurpassed levels of protection across a variety of driving conditions and temperatures.
- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- High shear stability helps maintain viscosity throughout oil drain period.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADE	5W-30
ACEA-16	C1
JAGUAR LAND ROVER	STJLR.03.5005
FORD	WSS-M2C934-B
JASO	DL-1

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT C1 (Typical Specification)
SAE Grades			5W-30
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.5
Viscosity Index	D2270	-	170
Density @15°C/ 60°F	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	228
Pour Point (max)	D97	°C	-42
TBN	D2896	Mg KOH/g	8
CCS, (°C)	D5293	m.Pa.5	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.