



SWIFT C1

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift C1 5W-30 is the new generation low SAPS fully synthetic engine oil designed to meet the needs of latest engine technologies of gasoline and diesel engines fitted with after treatment systems. It offers excellent performances at both low and high operating temperatures and long-term engine protection. Swift C1 utilizes low SAPS technology which helps prolong the life and maintain the efficiency of after-treatment systems in both diesel and gasoline powered automobiles.

APPLICATION:

Swift C1 5W-30 is recommended for applications requiring Ford WSS-M2C934-B and Jaguar Land Rover STJLR.03.5005 which includes Jaguar and Land Rover vehicles from January 2009 fitted with the 3.0 Litre V6 Diesel engine, and Mazda Diesel engines fitted with Diesel Particulate Filter (DPF) from 2005 requiring an ACEA C1 oil with SAE 5W-30 viscosity grade.

FEATURES & BENEFITS:

- Low SAPS formula helps maintain efficiency of diesel particulate filters and catalytic converters.
- Provides engine cleanliness and improved engine efficiency.
- Unsurpassed levels of protection across a variety of driving conditions and temperatures.
- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- High shear stability helps maintain viscosity throughout oil drain period.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADE	5W-30
ACEA-16	C1
JAGUAR LAND ROVER	STJLR.03.5005
FORD	WSS-M2C934-B
JASO	DL-1

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT C1 (Typical Specification)
SAE Grades			5W-30
Kinematic Viscosity @ 104°F /40°C	D445	cSt	59.1
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.5
Viscosity Index	D2270	-	170
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	0.846
Flash Point (min)	D92	°C	228
Pour Point (max)	D97	°C	-42
TBN	D2896	Mg KOH/g	8
CCS, (°C)	D5293	m.Pa.5	<6600 (-30°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Venom and its affiliates assume legal responsibility.