



SWIFT C2 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift C2 is a premium quality fully synthetic fuel economy engine oil blended for use in modern engines requiring low friction, low HTHS viscosity, and Mid-SAPS oil. The high-quality base stocks in combination with our most up-to-date additive technology ensure excellent aging stability, optimum wear protection, fuel savings, and outstanding cold-start properties over the entire oil change interval. Swift C2 meets the requirements of Euro VI emission regulations.

APPLICATION:

Recommended for diesel and petrol powered engines of FORD, JAGUAR, LAND ROVER, CHRYSLER and FIAT where ACEA C2 class fluid with SAE 0W-30 viscosity grade is recommended. SAE 5W-30 is specifically designed for vehicles of the PSA Group requiring lubricant meeting PSA B71 2290 standard, that demands protection against LSPI (Low-Speed Pre-Ignition). Fit for gasoline and diesel (HDI with or without DPF) engines, especially for the latest generation of turbo-charged gasoline engines with direct injection.

FEATURES & BENEFITS:

- Keeps engine clean by minimizing deposits.
- Optimized for emission control systems.
- Excellent cold start performance.
- Provides ultimate protection against wear under all operating conditions including start-start operation.
- Minimizes oil hydrodynamic friction, allowing fuel economy especially when oil is cold.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADE	0W-30	5W-30
ACEA-16	C2	C2
API	SN/CF	SN/CF
FORD	WSS M2C 950A	-
JAGUAR LAND ROVER	STJLR.03.5007	-
CHRYSLER	MS-13340/ MS-90047	-
FIAT	9.55535-GS1/DS1	9.55535-GS1/DS1
PSA	-	B71 2297-2290
RENAULT	RN0700	RN0700

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT C2 (Typical Specification)	
			0W-30	5W-30
SAE Grades				
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.2	9.9
Viscosity Index	D2270	-	180	162
Density @15°C/ 60°F	D4052	g/cm3	TBR	TBR
Flash Point (min)	D92	°C	224	222
Pour Point (max)	D97	°C	-42	-42
TBN	D2896	Mg KOH/g	8	8
CCS, (°C)	D5293	m.Pa.S	<6200 (-35°C)	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.