



SWIFT C3 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift C3 is a high-performance advanced fully synthetic new generation oil especially blended to meet demanding OEM specifications, including Volkswagen and Audi lubrication requirements. It is engineered to be used in gasoline and diesel engines of passenger cars and light vans equipped with Diesel Particulate Filter (DPP) and Three-Way Catalytic converter (TWC) systems.

APPLICATION:

Specifically designed for VAG Group recent cars (VOLKSWAGEN, AUDI, SKODA, and SEAT) fitted with Euro 4, Euro 5 and Euro 6 engines that require lubricants with low Sulfated Ash, low Sulphur and low Phosphorus rates (SAPS level). Swift C3 is fully backward compatible over previous VW oil standards such as VW 501 01, 502 00, 503 00 and 503 01 for Gasoline engines, and VW 505 00, 505 01, 506 00 and 506 01 for Diesel engines.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Excellent cold flow properties
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices.
- Helps protect engine against wear and corrosion
- Allows fuel consumption reduction and therefore minimizes green house gases emissions.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	5W-30
API	SN	SN
ACEA 2016	C3	C3
MB	229.51	229.51
VW	504 00/ 507 00	504 00/ 507 00
VW TL	52545	52195
BMW	LL-04	LL-04
PORSCHE	C30	C30

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT C3 (TYPICAL SPECIFICATION)	
			0W-30	5W-30
Grade				
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.7	11.7
Viscosity Index	D-2270	-	172	167
Density @15°C/ 60°F	D-4052	g/cm3	TBR	TBR
Flash Point (min)	D-92	°C	226	228
Pour Point (max)	D-97	°C	-42	-42
TBN	D-2896	Mg KOH/g	8.6	8.6
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.