



SWIFT C5 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift C5 is a premium quality fully synthetic mid-SAPS engine oil suitable for the latest engine technology. It ensures outstanding wear protection, strong durability, and exceptional fuel economy performance in the latest diesel and petrol engine fitted with Diesel Particulate Filters (DPF), Gasoline Particulate Filters (GPF), and Catalytic Converters. Swift C5 is compliant with Euro VI emission standards.

APPLICATION:

Swift C5 is recommended for new diesel and gasoline engines requiring an SAE 0W20 VW 508 00 / 509 00, VW TL 52577 or Porsche C20 specifications. VW 508 00 509 00 specification is a unique specification and therefore is not backward compatible with older engines.

FEATURES & BENEFITS:

- Strong LSPI performance
- Excellent low temperature flow
- Exceptional viscosity stability at high temperatures
- Outstanding oil film resistance and reduction in friction
- Optimised for strong oxidation performance
- Fuel economy benefits
- Protects against wear even at low viscosity
- Extended oil drain interval
- Enhanced acid neutralisation and TBN retention capability

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SN Plus
- ACEA C5
- VW 508 00 / 509 00
- VW TL52577
- Porsche C20

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT C5 (FULLY SYNTHETIC)
Grade			0W-20
Kinematic Viscosity @ 104°F / 40°C	D-7042	cSt	TBR
Kinematic Viscosity @ 212°F / 100°C	D-7042	cSt	8.8
Viscosity Index	D-2270	-	172
Density @ 15°C / 60°F	D-4052	g/cm ³	TBR
Flash Point (min)	D-92	°C	230
Pour Point (max)	D-97	°C	-42
TBN	D-2896	Mg KOH/g	8.2
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.