



## SWIFT FE FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

Swift FE is a premium quality fully synthetic, fuel-economy engine oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

### APPLICATION:

Swift FE 5W-20 is a Fuel Economy Engine Oil specially designed for OEMs requiring very low HTHS (High Temperature High Shear) viscosity oil ( $\geq 2.6$  mPa.s) : FORD, JAGUAR, LAND ROVER, CHRYSLER, JEEP, ... It is suitable for gasoline and diesel engines requiring a 5W-20 viscosity grade Fuel Economy Lubricant (ACEA A5 / B5 and ACEA A1 / B1 standards). Compatible with catalytic converters. Swift FE 0W-30 is universal, fuel-efficient engine oil. A premium product for gasoline and diesel engine passenger cars. Suitable for all petrol and diesel passenger cars with and without turbo charger, especially recommended for full synthetic all-season motor oils. Swift FE 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans designed for use of a low viscosity (HTHS  $>2.9$ ) motor oil where the viscosity and quality claims are appropriate.

### FEATURES & BENEFITS:

- Improved fuel economy
- Superior oil film strength under all engine operating conditions.
- Enhanced engine cleanliness and sludge prevention
- Enhanced cold start-up performance
- Enhanced wear protection
- Superior protection for exhaust catalyst and diesel particulate filter.

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-20	0W-30	5W-30
API	SN/CF	SL/CF	SL/CF
ACEA	A5/B5-16	A5/B5-16	A5/B5-16
FORD	WSS-M2C925-B	-	WSS-M2C913-D
JAGUAR LAND ROVER	STJLR.03.5004	-	STJLR.03.5003
MB	-	229.6	229.6
RENAULT	-	RN0700	RN0700
VOLVO	-	VCC 95200377	-

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT FE (Typical Specification)		
			5W-20	0W-30	5W-30
Grade					
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	8.0	10.2	10.2
Viscosity Index	D-2270	-	160	170	167
Density @15°C/ 60°F	D-4052	g/cm3	TBR	TBR	TBR
Flash Point (min)	D-92	°C	222	224	224
Pour Point (max)	D-97	°C	-42	-42	-42
TBN	D-2896	Mg KOH/g	10	10	10
CCS, (°C)	D-5293	m.Pa.S	6600 (-30°C)	6200 (-35°C)	6600 (-30°C)

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.