



SWIFT GT1 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Venom Swift GT1 is a high-performance advanced fully synthetic engine oil designed to provide outstanding performance for high-powered engines. It provides significant oil film resistance, outstanding engine cleanliness, wear protection, and strong durability. It has been specially designed for last-generation cars powered by gasoline or diesel engines, naturally aspirated or turbocharged, direct or indirect injection, requiring an ACEA C3 engine oil. Swift GT1 is compliant with EURO VI emission standards.

APPLICATION:

It is recommended for high-performance engines fitted with GPF (gasoline particulate filter) and SCR (Selective Catalyst Reduction), requiring an ACEA C3 engine oil. It is not backward compatible with vehicle engines requiring an A40, C30 or C20 specifications lubricant.

FEATURES & BENEFITS:

- Active detergent system helps to prevent buildup of deposits and sludge.
- Excellent thermal oxidation stability helps to reduce oil aging.
- Provides outstanding wear protection.
- Excellent cold flow properties helps to provide protection at start up..
- Enhanced frictional properties provide fuel economy improvement.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-40	5W-40
API	SN	SN
ACEA-16	C3	C3
MB	229.31, 229.52, 226.5	229.31, 229.52, 226.5
BMW	LL-04	LL-04
RENAULT	RN 0700/0710	RN 0700/0710
GM	DEXOS 2	DEXOS 2
PORSCHE	C40	C40
VW	511 00	511 00
FIAT	9.55535-S2/9.55535-T2	9.55535-S2/9.55535-T2

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT GT1 (Typical Specification)	
			0W-40	5W-40
SAE Grades				
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	14.1	13.9
Viscosity Index	D2270	-	190	173
Density @15°C/ 60°F	D4052	g/cm3	TBR	TBR
Flash Point (min)	D92	°C	226	228
Pour Point (max)	D97	°C	-42	-42
TBN	D2896	Mg KOH/g	8	8
CCS, (°C)	D5293	m.Pa.S	<6200 (-35°C)	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.