



## SWIFT RX SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

Swift RX is a high-performance semi synthetic engine oil fortified with a proven Metallo-organic anti-wear advanced additive system that protects engines under all operating conditions by providing excellent wear control in even the most sophisticated valve train mechanisms, including those with variable valve timing. It has been expertly engineered to help deliver superior cleaning power, wear protection, and outstanding performance. It helps resist degradation between oil changes, extending the time and mileage interval between oil changes.

### APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SM/CF.

### FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

### PERFORMANCE LEVELS: Meets and Exceeds:

- API SN/CF
- ACEA A3/B3
- MB 229.3
- Renault RN0700
- Renault RN0710
- VW 502 00
- VW 505 00

### TYPICAL PROPERTIES:

| PARAMETERS                         | TEST METHOD | UNIT     | SWIFT RX (SEMI SYNTHETIC) |               |
|------------------------------------|-------------|----------|---------------------------|---------------|
|                                    |             |          | 5W-30                     | 5W-40         |
| Grade                              |             |          | 5W-30                     | 5W-40         |
| Kinematic Viscosity @ 104°F /40°C  | ASTM D-7042 | cSt      | TBR                       | TBR           |
| Kinematic Viscosity @ 212°F /100°C | ASTM D-7042 | cSt      | 11.5                      | 15            |
| Viscosity Index                    | ASTM D-2270 | -        | 170                       | 176           |
| Density @15°C/ 60°F                | ASTM D-4052 | g/cm3    | TBR                       | TBR           |
| Flash Point (min)                  | ASTM D-92   | °C       | 232                       | 232           |
| Pour Point (max)                   | ASTM D-97   | °C       | -42                       | -42           |
| TBN                                | ASTM D-2896 | Mg KOH/g | 8                         | 8             |
| CCS, (°C)                          | ASTM D-5293 | m.Pa.S   | <6600 (-30°C)             | <6600 (-30°C) |

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.