



SWIFT SPECIFIC RN17

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift Specific RN17 is a high-performance engine oil developed to meet RN17, the latest specification for Renault vehicles (Renault, Dacia, Samsung) fitted with TGDI and EURO VI engines. The 100% Synthetic base stock provides a high thermal stability and low volatility which ensures an exceptional resistance to varnish and sludge formation and maintains engine cleanliness. Outstanding oxidation resistance of the lubricant results in extended oil drain intervals set by the car manufacturer. Swift Specific RN17 meets high quality standards, facilitating optimum engine performance and extended component life by virtue of fast and effective lubrication across a wide temperature range.

APPLICATION:

Swift Specific RN17 is designed for most gasoline engines (except Renault Sport & Alpine) and new Euro 6d diesel engines (2018 onwards) as well as all Diesel without DPF.

Velocity Specific RN 17 is suitable for use in vehicles where a Renault RN 17 specification SAE 5W/30 lubricant is required. The RN17 standard does not apply to diesel engines requiring RN0720.

FEATURES & BENEFITS:

- Advanced engine protection under all driving conditions.
- Prolongs the life and maintain the efficiency of particulate filters and catalytic converters.
- Keep engine clean from deposits for optimal efficiency and long life.
- Excellent protection against viscosity and thermal breakdown

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

| SAE GRADE | 5W-30 |
|-----------|--------|
| ACEA-16 | C3 |
| RENAULT | RN17 |
| MB | 226.52 |

TYPICAL PERFORMANCE:

| PARAMETERS | ASTM | UNIT | SWIFT SPECIFIC RN17 (Typical Specification) |
|-------------------------------------|-------|-------------------|---|
| SAE Grades | | | 5W-30 |
| Kinematic Viscosity @ 104°F / 40°C | D445 | cSt | TBR |
| Kinematic Viscosity @ 212°F / 100°C | D445 | cSt | 11.9 |
| Viscosity Index | D2270 | - | 172 |
| Density @ 15°C/ 60°F | D4052 | g/cm ³ | TBR |
| Flash Point (min) | D92 | °C | 226 |
| Pour Point (max) | D97 | °C | -42 |
| TBN | D2896 | Mg KOH/g | 8.5 |
| CCS, (°C) | D5293 | m.Pa.S | <6600 (-30°C) |

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.