



SWIFT SPECIFIC RN17 FE

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift Specific RN17 FE is a high-tech, low-friction engine oil specifically designed for RENAULT vehicles (Renault, Dacia, Samsung) fitted with gasoline and diesel engines requiring a Renault RN17 FE specification lubricant. The Mid-SAPS technology, in combination with unique low-friction properties, reduces fuel consumption and, thus minimizes pollutant emissions. The reduced levels of Sulfated Ash, Phosphorous and Sulphur of Swift Specific RN17 FE protects and extends lifetime of modern after-treatment systems such as DPF (Diesel Particulate Filter), SCR (Selective Catalyst Reduction) and GPF (Gasoline Particulate Filter).

APPLICATION:

Swift Specific RN17 FE is specifically designed for some RENAULT vehicles (Renault, Dacia, Samsung) marketed since 2018, requiring Renault RN17 FE performance level oil. The RN17 FE standard is not backward compatible to any other Renault standards such as RN0700, RN0710, RN0720, RN17 or RN17 RSA.

FEATURES & BENEFITS:

- Reduces the hydrodynamic friction of the oil, resulting in fuel savings.
- Extremely high ageing resistance, durability and robustness
- Reduced SAPS levels protect and extend lifetime of modern after treatment systems such as DPF, SCR and GPF.
- High thermal stability prevents varnish and sludge formation.
- Excellent cold flow properties.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADE	0W-20
ACEA-16	C5
API	SN
RENAULT	RN17 FE

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT SPECIFIC RN17 FE (Typical Specification)
SAE Grades			0W-20
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	8.5
Viscosity Index	D2270	-	179
Density @15°C/ 60°F	D4052	g/cm3	0.846
Flash Point (min)	D92	°C	224
Pour Point (max)	D97	°C	-42
TBN	D2896	Mg KOH/g	8.5
CCS, (°C)	D5293	m.Pa.S	<6200 (-35°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.