



SWIFT VS 16 MINERAL

PRODUCT DESCRIPTION:

Swift VS 16 is a high-performance mineral oil that is formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high-performance gasoline engine cars equipped with direct-injection, multi-valve & turbo-charged, and technologies.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SN.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SN/CF
- ACEA A3/B3/B4
- MB 229.1
- VW 505 00

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT VS 16 (MINERAL)	
			15W-40	20W-50
Grade			15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	177.9
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15.1	19.9
Viscosity Index	D2270	-	140	130
Density @15°C/ 60°F	D4052	g/cm3	TBR	TBR
Flash Point (min)	D92	°C	234	236
Pour Point (max)	D97	°C	-33	-24
TBN	D2896	Mg KOH/g	10	10
CCS, (°C)	D5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.