



SWIFT VS 16 PAO FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift VS 16 PAO is a premium quality lubricant formulated with PAO (Polyalphaolefin) base stocks which helps deliver outstanding engine protection in recent cars fitted with Gasoline and Diesel engines, naturally aspirated or turbo-charged, indirect or direct injection. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.

APPLICATION:

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels. Compatible for catalytic converters.

FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high-performance gasoline engine cars
- equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40
API	SL/CF	SN/CF
ACEA	A3/B4	A3/B4
VOLVO	95200356	-
Porsche	-	A40
MB	226.5 229.3 229.5	226.5 229.3 229.5
RENAULT	RN0700 RN0710	RN0700 RN0710
VW	502 00 505 00	502 00 505 00
BMW	LL-01	LL-01
PSA	-	-
Ford	-	WSS-M2C-937-A

TYPICAL SPECIFICATION:

PARAMETERS	ASTM	UNIT	SWIFT VS 16 PAO	
			0W-30	0W-40
Grade			0W-30	0W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.80	14.5
Viscosity Index	D-2270	-	180	190
Density @ 15°C/ 60°F	D-4052	g/cm ³	TBR	TBR
Flash Point (min)	D-92	°C	230	230
Pour Point (max)	D-97	°C	-42	-42
TBN	D-2896	Mg KOH/g	10	10
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.