



SWIFT VS11 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift VS11 is a premium quality fully synthetic motor oil blended from a high-performance additives system that actively helps keep the engine clean. It allows the product to provide higher levels of cleansing and protection. This oil is particularly suitable for turbo-compressed, multi-valve, and direct-injection engines. It meets the most difficult conditions of use (motorway, heavy urban traffic, etc.) during all seasons.

APPLICATION:

Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, four-stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- Superior wear and corrosion protection.
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity.
- Maintains power and economy by minimizing wear.
- Superior viscosity retention.
- Oxidation resistant.
- Engine Cleanliness and low combustion residue.

API LICENSE:

- SAE 5W-30
- SAE 5W-40



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40	5W-20	5W-30	5W-40
API	SL/CF	SL/CF	SL/CF	SL/CF	SL/CF
ACEA	A3/B3	A3/B3	A5/B5	A3/B3	A3/B3
MB	-	229.3, 226.5	-	-	229.3, 226.5
JASO	MA2	MA2	-	MA2	MA2
RENAULT	RN0700	RN 0700/0710	-	RN0700	RN 0700/0710
VW	501.01 / 505	501.01 / 505	-	501.01 / 505	501.01 / 505

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT VS11 FULLY SYNTHETIC (Typical Specification)				
			0W-30	0W-40	5W-20	5W-30	5W-40
SAE Grades							
Kinematic Viscosity @ 104°F / 40°C	D445	cSt	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D445	cSt	10.2	14.9	8.8	10.1	15
Viscosity Index	D2270	-	175	182	160	170	173
Density @ 15°C / 60°F	D4052	g/cm3	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	224	226	226	224	226
Pour Point (max)	D97	°C	-42	-42	-42	-42	-42
TBN	D2896	Mg KOH/g	8	8	8	8	8
CCS, (°C)	D5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.