



SWIFT VS13 SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Swift VS13 is a premium quality semi synthetic engine oil blended to help deliver outstanding engine protection and enhanced fuel economy. This oil is formulated to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low-temperature performance over the life of the oil.

APPLICATION:

Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, light truck gasoline engines, four-stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving
- Oil film able to withstand high operating temperatures
- Protects engines against deposits
- Standard drain interval

PERFORMANCE LEVELS: Meets and Exceeds:

- API SM/CF
- ACEA A3/B3
- VW 501.01 / 505.00
- RN 700, RN 710
- MB 229.3

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SWIFT VS13 (SEMI SYNTHETIC)	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	10.4	15.1
Viscosity Index	ASTM D-2270	-	154	159
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR	TBR
Flash Point (min)	ASTM D-92	°C	236	236
Pour Point (max)	ASTM D-97	°C	-39	-42
TBN	ASTM D-2896	Mg KOH/g	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	<7000 (-25°C)	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.