



SWIFT V55 MINERAL

PRODUCT DESCRIPTION:

Swift V55 is blended with high-quality mineral base stock and an advanced additive system to be used for passenger cars, light trucks as well as farm equipment, especially where a single type of oil is preferred. This oil contains inhibitors to combat acid formation, oxidation, and foaming.

APPLICATION:

Gasoline and light-duty diesel engines found in passenger cars, farm and construction equipment, stationary diesel engines and four-stroke engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SF/CD
- MIL-L-2104A

TYPICAL PROPERTIES:

| PARAMETERS | ASTM | UNIT | SWIFT V55 (MINERAL) | | | | |
|------------------------------------|--------|----------|---------------------|------|------------------|------------------|------------------|
| | | | 40 | 50 | 15W-40 | 20W-50 | 20W-60 |
| Grade | | | 40 | 50 | 15W-40 | 20W-50 | 20W-60 |
| Kinematic Viscosity @ 104°F /40°C | D-7042 | cSt | TBR | TBR | TBR | TBR | TBR |
| Kinematic Viscosity @ 212°F /100°C | D-7042 | cSt | 14.5 | 19.5 | 15.2 | 19.5 | 25.7 |
| Viscosity Index | D-2270 | - | 95 | 105 | 145 | 130 | 136 |
| Density @ 15°C/ 60°F | D-4052 | g/cm3 | TBR | TBR | TBR | TBR | TBR |
| Flash Point (min) | D-92 | °C | 250 | 254 | 224 | 236 | 232 |
| Pour Point (max) | D-97 | °C | -15 | -15 | -30 | -24 | -24 |
| TBN | D-2896 | Mg KOH/g | 6 | 6 | 6 | 6 | 6 |
| CCS, (°C) | D-5293 | m.Pa.S | N/A | N/A | <6800 (-20°C) | <9100 (-15°C) | <9200 (-15°C) |

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.