



SWIFT VS7 SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Swift VS7 is an advanced semi synthetic oil for gasoline and diesel engines having high aging resistance which effectively reduces carbon formation and high-temperature lacquer formation. It provides safe lubrication of the engine components. This oil contains low-ash additives which allow for prolonging the endurance of the catalyst.

APPLICATION:

Recommended for gasoline and light-duty diesel engines found in passenger cars, agriculture and construction equipment, stationary diesel engines and four-stroke engines. It can be comfortably used in mixed fleet.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SG/CF

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SWIFT VS7	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.9	14.90
Viscosity Index	ASTM D-2270	-	152	156
Density @15°C/ 60°F	ASTM D-4052	g/cm3	TBR	TBR
Flash Point (min)	ASTM D-92	°C	230	230
Pour Point (max)	ASTM D-97	°C	-36	-36
TBN	ASTM D-2896	Mg KOH/g	6	6
CCS, (°C)	ASTM D-5293	m.Pa.S	<6600 (-25°C)	<6700 (-25°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.