



SWIFT VS9 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift VS9 is a premium quality fully synthetic engine oil blended with advanced performance base stocks and the latest additives system which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

APPLICATION:

Recommended for all naturally aspirated, fuel injected, turbo-charged and multi-valve passenger car engines without particulate filters.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Outstanding wear and friction protection
- Excellent detergency and dispersancy
- Easy start at low temperatures
- Excellent protection against sludge and varnish build-up

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-30	5W-40
API	SJ/CF	SJ/CF
ACEA	A1/B1	A3/B3
ILSAC	GF-2	GF-2
FORD	WSS-M2C-913A/913B	-

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	SWIFT VS9 (FULLY SYNTHETIC)	
			5W-30	5W-40
SAE Grades			5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.1	14.5
Viscosity Index	D2270	-	165	173
Density @15°C/ 60°F	D4052	g/cm3	TBR	TBR
Flash Point (min)	D92	°C	224	224
Pour Point (max)	D97	°C	-42	-42
TBN	D2896	Mg KOH/g	6	6
CCS, (°C)	D5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.