



SWIFT XTŁ

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Swift XTŁ is a fully synthetic MID SAPS lubricant for gasoline and diesel engines, including the ones complying with ACEA C2/C3 standards. Swift XTŁ is formulated to reduce pollutant emissions, such as HC, NOx, CO, and particles, and to protect and ensure the longevity of after-treatment antipollution systems, such as Particulate Filters (GPF, DPF) and Three-Way Catalysts. Synthetic base oils together with the latest additive technology, guarantee a motor oil that provides exceptional protection against wear and reduces oil and fuel consumption.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol engine oils, as well as the requirements of many major American and European engine manufacturers. Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Excellent cold flow properties
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices.
- Helps protect engine against wear and corrosion
- Allows fuel consumption reduction and therefore minimizes green house gases emissions.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

| SAE GRADES | 5W-40 | 5W-30 |
|------------|----------------|----------------|
| API | SN PLUS/ SP | SN PLUS/ SP |
| ACEA 2016 | C3 | C3/C2 |
| BMW | LL-04 | LL-04 |
| MB | 229.51/ 229.52 | 229.51/ 229.52 |
| OPEL | OV 040 1547 | OV 040 1547 |
| RENAULT | RN0700/RN0710 | RN0700/RN0710 |

TYPICAL PERFORMANCE:

| PARAMETERS | ASTM | UNIT | SWIFT XTŁ (TYPICAL SPECIFICATION) | |
|------------------------------------|--------|----------|-----------------------------------|-------|
| | | | 5W-40 | 5W-30 |
| Grade | | | | |
| Kinematic Viscosity @ 104°F /40°C | D-7042 | cSt | TBR | TBR |
| Kinematic Viscosity @ 212°F /100°C | D-7042 | cSt | 13.5 | 11.8 |
| Viscosity Index | D-2270 | - | 180 | 179 |
| Density @15°C/ 60°F | D-4052 | g/cm3 | TBR | TBR |
| Flash Point (min) | D-92 | °C | 224 | 220 |
| Pour Point (max) | D-97 | °C | -42 | -42 |
| TBN | D-2896 | Mg KOH/g | 9 | 9 |
| CCS, (°C) | D-5293 | m.Pa.S | <6600 | <6600 |

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.