



TURBO 3000 MINERAL

PRODUCT DESCRIPTION:

Turbo 3000 is a mineral multi-grade diesel engine oil designed using high-quality base oils and additives which are recommended for the lubrication of diesel engines and naturally aspirated gasoline engines used in commercial and passenger vehicles operating under mild driving conditions.

APPLICATION:

Recommended for the lubrication of diesel / gasoline engines used in trucks and passenger cars operating under mild driving conditions. It can also be used in agriculture equipment, medium-duty trucking, off-road vehicles, construction and quarrying, and certain transmission and mobile hydraulic systems where use of monograde engine oils is recommended by the equipment manufacturer.

FEATURES & BENEFITS:

- Good protection against rust and corrosion
- Thermal and oxidation stability
- Controls sludge build up and deposits
- Long equipment life and reduced maintenance cost.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CC/SC
- MIL-L-2104B

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	TURBO 3000 (MINERAL)				
			15W-40	20W-50	20W-60	40	50
Grade			15W-40	20W-50	20W-60	40	50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	15.45	20.3	24.2	15.5	20.2
Viscosity Index	D-2270	-	140	131	150	105	110
Density @15°C/ 60°F	D-4052	g/cm3	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D-92	°C	236	236	230	242	246
Pour Point (max)	D-97	°C	-33	-24	-24	-15	-15
TBN	D-2896	Mg KOH/g	3.5	3.5	3.5	3.5	3.5
CCS, (°C)	D-5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)	<9500 (-15°C)	-	-

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.