



## TURBO 8000 MINERAL

### PRODUCT DESCRIPTION:

Turbo 8000 CF-2 two stroke diesel engine oil is formulated with high-quality base oil and a multi functional additive system. Formulated especially for severe duty, two-stroke cycle diesel engine applications.

### APPLICATION:

Severe duty two-stroke cycle diesel engine applications that require a monograde API CF-2 or CD-II oil.

### FEATURES & BENEFITS:

- Excellent deposit control characteristics reduce the build up of combustion chamber and valve-seat deposits, reducing wear and ensuring effective engine operation.
- Medium-ash formulation reduces the incidence of valve guttering.
- Good thermal and oxidation stability together with good detergency properties, ensure the oil does not break down at high temperatures keeps the engine clean and extends component life.
- Excellent lubricity and antiwear properties protect against engine wear and extend engine life.
- Excellent anti-rust performance and acid neutralizing properties protect the engine from rust and corrosion.

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- CF-2

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	TURBO 8000
Grade			50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	20.5
Viscosity Index	D-2270	-	110
Density @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	D-92	°C	246
Pour Point (max)	D-97	°C	-15
TBN	D-2896	Mg KOH/g	10

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.