



TURBO X-MAX FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Turbo X-Max is a fully synthetic heavy-duty diesel engine oil that combines advanced engine protection for modern fewer emissions vehicles with enhanced fuel economy potential in modern diesel engines operating in severe conditions. Turbo X-Max meets the API CJ-4 specification by utilizing state-of-the-art technology to deliver exceptional performance in modern low-emission engines, including those with Exhaust Gas Recirculation (EGR), After-Treatment Systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's).

APPLICATION:

Turbo X-Max is recommended for use in 4-stroke diesel engines, including modern low emission engines with Exhaust Gas Recirculation (EGR), After-Treatment systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's). Recommended for on-highway engines operating in both high speed / high load and stop-and-go conditions, and Off-highway engines operating in severe low speed/ heavy load conditions. Also suitable for high-performance gasoline engines and mixed fleets.

FEATURES & BENEFITS:

- Prevents premature DPF plugging and shortened maintenance intervals
- Minimizes piston and combustion chamber deposits
- Fights Sludge and Varnish
- Excellent against engine wear due to soot formation
- Excellent oxidation, foam, and corrosion inhibition
- Provides faster, and safe starts during extreme temperatures and increases thermal and oxidation stability at extreme high temperatures
- Extended engine life

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CJ-4/SN
- ACEA E9
- MB 228.31
- Caterpillar ECF-3
- MAN M3477/3575
- VOLVO VDS-4
- Renault RLD-3
- DDC 93K218
- Mack EO-O PP
- Cummins CES 20081
- DEUTZ DQC III-10 LA
- FORD WSS-M2C171-F1

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	Turbo X-Max (FULLY SYNTHETIC)			
			0W-30	0W-40	5W-30	5W-40
Grade			0W-30	0W-40	5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.85	14.9	11.8	15
Viscosity Index	D-2270	-	175	180	170	173
Density @15°C/ 60°F	D-4052	g/cm3	TBR	TBR	TBR	TBR
Flash Point (min)	D-92	°C	234	230	234	232
Pour Point (max)	D-97	°C	-42	-42	-42	-42
TBN	D-2896	Mg KOH/g	9.9	9.9	9.9	9.9
CCS, (°C)	D-5293	m.Pa.S	6200 (-35°C)	6200 (-35°C)	6600 (-30°C)	6600 (-30°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.