



TURBO X-CESSTM SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Turbo X-CESSTM is an advanced quality semi synthetic diesel engine oil blended with premium quality base stocks which are enhanced with an advanced multi-functional additive system. This oil is fuel-saving and reduces maintenance expenses for machines and engines. It resists oil thickening and the formation of carbon, varnish, and sludge deposits. It also helps prolong engine life.

APPLICATION:

Recommended for modern heavy-duty engines, wide range of turbo-charged or naturally aspirated diesel engines as well as all kinds of gasoline engines, generators, trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. The oil is suitable for high speed, four stroke cycle diesel engines used on heavy-duty applications. This oil is also an excellent choice for mixed fleet services.

FEATURES & BENEFITS:

- Extended drain intervals.
- Resists oil thickening and the formation of carbon, varnish and sludge deposits.
- Good viscosity stability.
- Prolonged engine life.
- Properly balanced detergency and dispersancy ensures a clean engine.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CG-4/SJ
- MB 228.3
- ACEA A3/B4
- MAN 3275
- VOLVO VDS
- MTU Type-2
- MACK EO-L
- Allison C4

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	TURBO X-CESSTM (SEMI SYNTHETIC)	
			10W-30	10W-40
Grade				
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.75	15.6
Viscosity Index	D-2270	-	154	157
Density @ 15°C/ 60°F	D-4052	g/cm3	TBR	TBR
Flash Point (min)	D-92	°C	236	234
Pour Point (max)	D-97	°C	-39	-39
TBN	D-2896	Mg KOH/g	9.5	9.5
CCS, (°C)	D-5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.