



## VENOM MARINE 2T

### PRODUCT DESCRIPTION:

Venom Marine 2T is high-performance two-stroke outboard marine engine oil conforming to TC-W2; superior quality ash-less two-stroke lubricant designed to meet the most critical requirements of all air-cooled and water-cooled outboard engines.

### APPLICATION:

Venom Marine 2T is recommended for and meets the requirements of all major outboard engine manufacturers: Chrysler, Evinrude, Johnson, Mercury, Mariner, U.S. Marine/Force, Sears, OMC, Suzuki, Yamaha, Nissan, Daihatsu, or wherever NMMA TC-WII or TC-W oils may be used. It is also suitable for motorcycles, lawn mowers, scooters, golf cars, snowmobiles, personal water craft, chain saws, and other two-stroke powered equipment.

### FEATURES & BENEFITS:

- Minimizes piston rings from sticking to keep the engine operating smoothly and efficiently
- Protects against piston and combustion chamber deposits, rust, and corrosion
- Protects the piston from scuffing and pre-ignition problems and assures good low temperature fluidity
- Spark-plug fouling and carbon deposits are prevented so that power can be maintained longer
- Mixes easily with fuel for premix applications

### PERFORMANCE STANDARDS: Meets and Exceeds:

- NMMA TC-W2, TC-W

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MARINE 2T
Grade			TC-W2
Kinematic Viscosity @ 104°F / 40°C	ASTM D-445	cSt	TBR
Kinematic Viscosity @ 212°F / 100°C	ASTM D-445	cSt	8.8
Viscosity Index	ASTM D-2270	-	128
Density @60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	120
Pour Point (max)	ASTM D-97	°C	-36

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.