



## VENOM MARINE 2T PLUS

### PRODUCT DESCRIPTION:

Venom Marine 2T Plus is an advanced, two-stroke, marine outboard engine oil engineered with a special ash-less additive system. It is designed for engines requiring NMMA TC-W3 performance lubricants, operating in all service conditions. It is pre-diluted with high flash point solvent to facilitate mixing with petrol at all temperatures.

### APPLICATION:

Venom Marine 2T Plus is recommended for use in two-stroke engines where TC-W3 or earlier lubricants are recommended. These applications include outboard engines, motorcycles, lawn mowers, scooters, golf carts, chain saws, and other two-stroke powered equipment. Venom Marine 2T Plus is well suited for engines using oil injection systems with fuel/oil mixture ratios of up to 150:1. Venom Marine 2T Plus has excellent low temperature mixing characteristics that make it suitable for use in cold climate conditions.

### FEATURES & BENEFITS:

- Maintains high-power output
- Superior piston cleanliness and minimizes deposit formation
- Reduces maintenance cost due to enhanced lubricity
- Trouble free operation
- Maximizes spark plug life

### PERFORMANCE STANDARDS: Meets and Exceeds:

- NMMA TC-W3
- API TC

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MARINE 2T PLUS
Grade			TC-W3
Kinematic Viscosity @ 104°F / 40°C	ASTM D-445	cSt	TBR
Kinematic Viscosity @ 212°F / 100°C	ASTM D-445	cSt	9,1
Viscosity Index	ASTM D-2270	-	127
Density @60°F	ASTM D-4052	g/cm3	TBR
Flash Point (min)	ASTM D-92	°C	126
Pour Point (max)	ASTM D-97	°C	-36

### DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

### HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

### PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

### STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.