



SWIFT RX

FULLY SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

SWIFT RX is a high-performance lubricant enhanced with a proven metallo-organic anti-wear additive system that ensures engine protection under all operating conditions. It offers exceptional wear control, even in advanced valve train systems such as those with variable valve timing. Expertly formulated, it delivers powerful cleaning action, excellent wear protection, and top-tier performance. Its resistance to degradation helps extend the interval and mileage between oil changes.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an oil meeting API SN/CF specification.

FEATURES & BENEFITS:

- Outstanding wear protection under a wide variety of operating conditions.
- Special cleaning additive to help prevent the formation of sludge and harmful deposits.
- Optimal engine operating temperature, owing to thermal control formula.
- Limits formation of deposits on the most loaded engine parts.
- Provides safe operation of catalytic exhaust convertors.
- Resistant to extreme thermal load, due to high quality of base oil.
- Enables fast and easy start in extreme temperature conditions.
- High performance extended drain formulation helps offer optimum engine uptime.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-20	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
API	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF	SN/CF
ILSAC	GF-5	GF-5	-	-	-	-	-	-
ACEA	-	-	A3/B4-12	A3/B4-12	A3/B4-12	A3/B4-12	A3/B4-12	A3/B4-12
MB	-	-	229.3	229.3	229.3	229.3	229.3	229.3
VW			502 00/ 505 00	502 00/ 505 00				
RENAULT			700/710	700/710	700/710	700/710	700/710	700/710

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SWIFT RX							
			0W-20	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
Grade										
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	8.4	8.5	11.8	15	11.8	15.1	15.4	20.1
Viscosity Index (min)	ASTM D2270	-	150	150	160	160	145	145	135	120
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	ASTM D97	°C	-39	-39	-39	-39	-36	-36	-33	-24

DISCLAIMER:

The test data mentioned above is not a definitive specification but serves as an indication and may fluctuate within acceptable production tolerances. Venom retains the right to alter this test data. Any updated information will replace previous versions, so please consult the latest Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Extended and repeated exposure to oil can lead to skin conditions. Please avoid contact. If you do come into contact with oil, wash the affected area immediately with soap and water. Do not dispose of used oil down drains or into the environment; instead, take it to an authorized used oil collection point.

HEALTH & SAFETY:

This product is unlikely to pose significant health or safety risks when used properly in the recommended application and with good personal hygiene practices. For more information, please refer to the Safety Data Sheet (SDS), which is available upon request from your local sales office.

PROTECT THE ENVIRONMENT:

Please take used oil to an authorized collection point and adhere to local regulations. Do not discharge it into drains, soil, or water.

STORAGE:

We recommend storing all packages in a covered area. If outdoor storage is necessary, drums should be positioned horizontally to prevent water ingress and protect the markings. Products should never be stored above 60°C or exposed to direct sunlight or freezing temperatures.