



# 1) IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY

Product Name: WAXOL LX 460 EP NLGI 2 Company Identification: REXOL FZC

# 1.1 Details of the Supplier of the Safety Data Sheet

Supplier: REXOL FZC, PO Box 52341, Plot 1F-09B, 09B

Hamriyah Free Zone, Sharjah, United Arab Emirates

Supplier Phone & Email Address: Phone: +971 6 561 8895 Email: info@venomoil.de

Date of Issue 01-DEC-2022 Date of Revision 01-OCT-2023 Prepared by: **REXOL FZC** 

### 1.2 Emergency Telephone Number

Emergency United Arab Emirates, Government of Sharjah, Hamriyah Free Zone

Authority, and SAFETY PH NO. +971 6 526 1666 (24x7) Telephone Number:

EMERGENCY PH NO. +971 6 526 2111 (24x7)

#### 2) Hazard Identification

#### 2.1 Classification of the Substance / Mixture

**Product Definition:** Mixture

Classification according to Regulation (EC) No. 1272/2008

[CLP/GHS]

Not Classified

1999/45/EC [DPD]

Classification according to Directive The product is not classified as dangerous according to Directive

1999/45/EC and its amendments.

#### 2.2 Label Elements

Signal Word: No signal words.

Hazard Statements: No known significant effects or critical hazards.

**Precautionary Statements:** 

Prevention Not applicable. Response Not applicable. Storage Not applicable. Disposal Not applicable. Supplemental Label Elements: Not applicable.

Special Packaging Requirements:

Containers to be fitted Not applicable.

with child-resistant

#### **Material Safety Data Sheet**



fastenings

Tactile Warning of Danger: Not applicable.

# 3) Composition/Information on Ingredients

Ingredient name	CAS NUMBER	AMOUNT %		
Base Oil	Mixture	70% - 95%		
Performance Additives	Mixture	5% - 30%		

The product is not considered to be hazardous and does not contain hazardous components at or above regulated limits.

#### 4) FIRST & MEASURES

General Information: Remove contaminated clothing immediately, to be disposed of or washed before reuse.

**Inhalation:** If inhaled, provide fresh air, warmth, rest and medical advice if necessary.

**Skin Contact:** Clean areas of skin affected with soap and copious water. If necessary seek medical advice.

**Eye Contact:** In case of contact with eyes, rinse immediately with plenty of water until irritation subsides.

**Ingestion:** If exposed person feels like nauseating or vomiting seek medical help immediately.

#### 5) FIRE FIGTING MEASURES

Extinguishing Media: To suit local surroundings (e.g. water spray, carbon dioxide foam, chemical powder). Special Exposure: Hazard Decomposition products released in a fire should be considered as probably harmful if inhale (refer to Stability and Reactivity section). Protective Equipment: Wear self-contained breathing apparatus.

# 6) ACCIDENTAL RELEASES MEASURES

Methods for Cleaning up take up with absorbent material, example sawdust and dispose of as prescribed. Do not allow to mix with water or discharge in drainage or stream.

### 7) HANDLING & STORAGE

Advice on Safe Handling: Wear PPE as per company policy and practice good hygiene and safety practice. Avoid temperatures > 120°C

Advice on Protection against Fire & Explosion: N/A

Storage Conditions - Ensure adequate ventilation of storage area. Keep container tightly closed, cool

# 8) EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Controls:** Monitoring of the workplace should be considered in accordance with EH40 (or equivalent) Controls. LTEL (8 hour TWA): 5 mg/m 3 (EH40, 1998) STEL (15 min): 10 mg/m 3 (EH40, 1998) OES data for oil mist, mineral. In addition the Reciprocal Calculation Procedure (RCP) for hydrocarbons should be considered (EH40, 1998).

**Engineering Controls:** Ensure adequate ventilation of working area e.g. Local Exhaust Ventilation.

MSDS: WAXOL LX 460 EP NLGI 2

Prepared by: REXOL FZC, Sharjah, UAE





**Personal Protection:** Observe normal safety standards for handling chemicals. Avoid inhalation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment appropriate for the task e.g. gloves, safety goggles, respirators (e.g. if ventilation is inadequate), appropriate overalls. ISO9001:2015

# 9) PHYSICAL & CHEMICAL PROPERTIES

NLGI GRADE	2		
COLOR	Light Brown		
TEXTURE	Smooth & Homogenous		
PENETRATION mm@25°C	265 - 295		
OPERATING TEMPERATURE	-20 to 150		

### 10) STABILITY & REACTIVITY

Stability: N/A

Thermal Decomposition: Not determined Conditions to Avoid: N/A

Material to Avoid: N/A

Hazardous Reactions: The product does not undergo hazardous polymerization. Hazardous Decomposition products: Oxides of carbon, aldehydes, ketones, and of hydrogen sulphide plus combustion products of nitrogen and sulphur.

# 11) TOXICOLOGICAL INFORMATION

Acute Toxicity No acute toxicological data are available. LD 50 rat

(oral): N/A

LD 50 rat (i.v.): N/A

Dermal Compatibility N/A

Mucous Membrane Compatibility: N/A

### 12) ECOLOGICAL INFORMATION

Eco toxicology Eco toxicological data are not available

Further Ecological Information: N/A

Further Information. The product must not enter ground or waste water. If this occurs, inform the local authority at once.

#### 13) DISPOSAL CONSIDERATIONS

Advice on Disposal: In accordance with national and local authority regulations, e.g. special waste or incineration after consultation with the operators.

MSDS: WAXOL LX 460 EP NLGI 2

Prepared by: REXOL FZC, Sharjah, UAE





# 14) TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA	
14.1 UN Number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN Proper Shipping Name	-	-	-	-	
14.3 Transport Hazard Class	-	-	-	-	
14.4 Packing Group	-	-	-	-	
14.5 Environmental Hazards	No	No	No	No	
Additional Information	-	-	-	-	
14.6 Special Precautions for User	Not available				

### 15) REGULATORY INFORMATION

Classification & Labeling: Product is not classified in accordance with the Chemical (Hazard

Information and

Packaging for Supply Regulations (CHIP 97). Risk

Phrases: N/A

Safety Phrases: N/A

#### **Notice to Reader:**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from REXOL FZC. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The REXOL FZC shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the REXOL FZC to ensure that this document is the most current available. Alteration of this document is strictly prohibited